

RADCO TEST REPORT
Report No. RAD-1003
Project No. C-4109
Lab No. L-1315

THERMAL RESISTANCE PROPERTIES
OF
EXPANDED POLYSTYRENE KORFIL BLOCK INSERTS

Prepared for

KORFIL INCORPORATED
FREIGHT HOUSE ROAD, P.O. BOX 1000
WEST BROOKFIELD, MA 01585

by

R A D C O

Resources Applications, Designs and Controls, Inc.
Listing and Testing Division
P.O. Box 5506
Carson, CA 90749

Prepared by:

Chris Hernandez
Chris Hernandez
Technician, Insulation
Testing Laboratory

Reviewed/Submitted by:

Michael L. Ziemer
Michael L. Ziemer, P.E.
Sr. Vice President -
Operations

Issued: December 1989

TABLE OF CONTENTS

	Page No.
1.0 INTRODUCTION	1
2.0 TEST MATERIAL	1
3.0 TEST METHOD	1
4.0 TEST RESULTS	1

1.0 INTRODUCTION

At the request of Korfil., Inc., RADCO has performed thermal transmission testing (ASTM C-518) on specimens cut from 12"M (PCM) expanded polystyrene (EPS) Korfil Block Inserts.

2.0 TEST MATERIAL

Korfil, Inc. selected the above referenced inserts and shipped them to the RADCO physical testing laboratory in Gardena, California. Eight 12"M (PCM) EPS Korfil block inserts, were received by RADCO on November 14, 1989. The Korfil Block inserts were identified as 12"M (PCM) lot #11658 manufactured from Arco 35 MBK beads. RADCO cut the necessary test specimens from the above referenced EPS Korfil Block inserts.

3.0 TEST METHOD

Testing for thermal resistance was performed utilizing the Dynatech Rapid "k" heat flow meter in accordance with ASTM C-518 test procedures.

4.0 TEST RESULTS

The "k" and "R" values for the two specimens tested per ASTM C-518 are as follows.

(EPS) Korfil Block Insert - @ 75°F mean temperature
Lot #11658 "k" per inch = 0.237
BTU/(hr·ft²·°F)
Test performed 12/6/89 "R" per inch = 4.219
(hr·ft²·°F)/BTU
at a test density of 1.15 lb/ft³,
and thickness of 0.528 (Δ x)

(EPS) Korfil Block Insert - @ 75°F mean temperature
Lot #11658 "k" per inch = 0.239
BTU/(hr·ft²·°F)
Test performed 12/7/89 "R" per inch = 4.184
(hr·ft²·°F)/BTU
at a test density of 1.12 lb/ft³,
and thickness of 0.538 (Δ x)